



Model	Voltage	Current	Motor power		Outlet		Rated capacity	Rated head	Max capacity	Max Head	Impeller Passage	Cable
	V	A	kW	HP	in	mm	m³/h	m	m³/h	m	mm	mm²
50C2.75	380	2	0.75	1	2	50	10	8	24	12	20	4G1.0
50C2.75S	220	5.2	0.75	1	2	50	10	8	24	12	20	3G1.0
50C21.1	380	2.8	1.1	1.5	2	50	15	9	27	15	20	4G1.0
50C21.1S	220	7.2	1.1	1.5	2	50	15	9	27	15	20	3G1.0
50C21.5	380	3.2	1.5	2	2	50	25	8	31	13	25	4G1.0
80C21.5	380	3.2	1.5	2	3	80	40	6	52	13	25	4G1.0
50C22.2	380	5	2.2	3	2	50	25	12	35	17	25	4G1.0
80C22.2	380	5	2.2	3	3	80	40	9	61	17	25	4G1.0
80C23.0	380	6.5	3.0	4	3	80	42	11	67	21	30	4G1.5
80C24.0	380	8.9	4.0	5.5	3	80	50	12	79	24	30	4G1.5
100C25.5	380	11.7	5.5	7.5	4	100	65	13	107	27	35	4G2.5
100C27.5	380	15.7	7.5	10	4	100	85	13	120	30	35	4G2.5